

**Tab.2 Dimensions - Line pipe HOT ROLLING CPE MILL**

Nominal	OD		WT		Weight		Lmax		Identification		
	in	mm	in	mm	lb/ft	kg/m	ft	m	API	STD/XS/XS	Sch.
1/2	0.840	21.3	0.109	2.77	0.85	1.27	29.5	9	5L	STD	40
			0.147	3.73	1.09	1.62			5L	XS	80
3/4	1.050	26.7	0.113	2.87	1.13	1.69	29.5	9	5L	STD	40
			0.154	3.91	1.48	2.20			5L	XS	80
1	1.315	33.4	0.133	3.38	1.68	2.50	29.5	9	5L	STD	40
			0.179	4.55	2.17	3.24			5L	XS	80
			0.250	6.35	2.85	4.24					160
1 1/4	1.660	42.2	0.140	3.56	2.27	3.39	29.5	9	5L	STD	40
			0.191	4.85	3.00	4.47			5L	XS	80
			0.250	6.35	3.77	5.61					160
1 1/2	1.900	48.3	0.145	3.68	2.72	4.05	39.4	12	5L	STD	40
			0.200	5.08	3.63	5.41			5L	XS	80
			0.281	7.14	4.86	7.25					160
2	2.375	60.3	0.154	3.91	3.66	5.44	39.4	12	5L	STD	40
			0.172	4.37	4.05	6.03			5L		
			0.188	4.78	4.40	6.54			5L		
			0.218	5.54	5.03	7.48			5L	XS	80
			0.250	6.35	5.68	8.45			5L		
			0.344	8.74	6.29	11.11					160
2 1/2	2.875	73.0	0.216	5.49	6.14	9.14	39.4	12	5L	STD	40
			0.250	6.35	7.02	10.44					160
			0.276	7.01	7.67	11.41			5L	XS	80
3	3.500	88.9	0.216	5.49	7.58	11.29	39.4	12	5L	STD	40
			0.300	7.62	10.26	15.27			5L	XS	80
			0.438	11.13	14.34	21.35					160
3 1/2	4.000	101.6	0.226	5.74	9.12	13.57	39.4	12	5L	STD	40
			0.318	8.08	12.52	18.64			5L	XS	80
4	4.500	114.3	0.237	6.02	10.80	16.08	39.4	12	5L	STD	40
			0.337	8.56	15.00	22.32			5L	XS	80
			0.438	11.13	19.02	28.32					120

**Note:** Lengths: 6m or 9m or 12m