

Tab. 3 HOT ROLLED MECHANICAL TUBES acc. ASTM A519

WT	mm	2.41	2.8	3.8	4.8	5.6	7.6	9.5	12.7	15.9	19.1	22.2	25.4	28.6	31.8	34.9	38.1	41.3	44.5	47.6	50.8	54.0	57.2	
	in	0.095	0.110	0.150	0.189	0.220	0.299	0.374	0.500	0.626	0.752	0.874	1.000	1.126	1.252	1.374	1.500	1.626	1.752	1.874	2.000	2.126	2.252	
OD		Length max [m]																						
mm	in																							
21.3	0.838	12.0	12.0	12.0				Notes: 1. Yellow marked sizes with inside polygon and not according ASTM. 2. ASTM A519 cold worked, dimension 108÷200mm, are available only with <i>the producer's consulting</i> . 3. Weight: We=10.68 (OD-WT)xWT [lbs/ft]; We=0.0246615x(OD-WT)xWT [kg/m].																
26.7	1.051	12.0	12.0	12.0																				
33.4	1.315	12.0	12.0	12.0	12.0																			
42.2	1.661	12.0	12.0	12.0	12.0	12.0																		
48.3	1.902	12.0	12.0	12.0	12.0	12.0																		
57.2	2.252		12.0	12.0	12.0	12.0	12.0																	
60.3	2.374		12.0	12.0	12.0	12.0	12.0	12.0	12.1	12.1														
63.5	2.500		12.0	12.0	12.0	12.0	12.0	12.0	12.1	12.1														
69.9	2.752		12.0	12.0	12.0	12.0	12.0	12.0	11.8	12.1	12.1													
73.0	2.874		12.0	12.0	12.0	12.0	12.0	11.0	11.5	11.9	12.1													
76.2	3.000		12.0	12.0	12.0	12.0	12.0	11.0	11.3	11.7	12.1													
82.6	3.252		12.0	12.0	12.0	12.0	12.0	11.0	11.4	11.8	12.1	12.1	12.1											
88.9	3.500		12.0	12.0	12.0	12.0	12.0	10.5	11.4	12.0	12.1	12.1	12.1											
95.3	3.752			12.0	12.0	12.0	12.0	10.0	11.1	11.5	11.8	12.0	11.8											
101.6	4.000			12.0	12.0	12.0	12.0	10.0	9.5	9.5	9.5	9.5	9.4	8.7										
108.0	4.252			12.0	12.0	12.0	12.0	10.0	9.5	9.5	9.5	9.5	9.3	8.6										
114.3	4.500			12.0	12.0	12.0	12.0	11.0	9.5	9.5	9.5	9.5	9.5	9.5	8.9									
120.7	4.752							11.0	9.5	9.5	9.5	9.5	9.5	9.0	8.2	7.8								
127.0	5.000							12.0	9.3	9.5	9.5	9.5	9.5	9.0	8.2	7.7								
133.4	5.252							12.0	9.3	9.5	9.5	9.5	9.3	8.5	7.7	7.2								
139.7	5.500							12.0	9.3	9.5	9.5	9.5	9.5	8.9	8.3	7.8	7.4							
141.3	5.563							12.0	9.3	9.5	9.5	9.5	9.5	8.9	8.3	7.8	7.4							
146.1	5.752							12.0	9.3	9.5	9.5	9.5	9.5	8.7	7.8	7.4	7.0							
152.4	6.000							12.0	9.3	9.5	9.5	9.5	9.4	9.2	8.6	8.0	7.7	7.2	7.0					
158.8	6.252							12.0	11.0	9.5	9.5	9.5	9.4	9.1	8.9	8.5	8.0	7.5	7.0	6.7				
165.1	6.500							12.0	12.0	9.3	9.5	9.5	9.3	9.0	8.8	8.5	8.0	7.6	7.1	6.8				
168.3	6.626							12.0	12.0	9.3	9.5	9.5	9.5	9.1	8.9	8.3	7.8	7.2	7.0	6.7				
171.5	6.752							12.0	12.0	9.3	9.5	9.5	9.5	9.1	8.9	8.3	7.8	7.2	7.0	6.7				
177.8	7.000							12.0	11.9	9.3	9.5	9.5	9.2	9.0	8.7	8.6	8.0	7.2	7.4	7.1				
184.2	7.252									9.3	9.5	9.5	9.2	9.0	8.7	8.6	8.0	7.2	7.4	7.1				

Tab. 3 HOT ROLLED MECHANICAL TUBES acc. ASTM A519 - table continued

WT	mm	2.41	2.8	3.8	4.8	5.6	7.6	9.5	12.7	15.9	19.1	22.2	25.4	28.6	31.8	34.9	38.1	41.3	44.5	47.6	50.8	54.0	57.2
	in	0.095	0.110	0.150	0.189	0.220	0.299	0.374	0.500	0.626	0.752	0.874	1.000	1.126	1.252	1.374	1.500	1.626	1.752	1.874	2.000	2.126	2.252
OD		Length max [m]																					
mm	mm																						
190.5	7.500									9.3	9.5	9.4	9.1	8.9	8.7	8.5	8.3	8.0	7.5	7.3	7.0		
193.7	7.626									9.3	9.5	9.4	9.1	8.9	8.7	8.5	8.3	8.0	7.5	7.3	7.0		
196.9	7.752										9.3	9.3	9.1	8.9	8.6	8.5	8.4	8.0	7.6	7.4	7.1	6.7	6.6
203.2	8.000										9.3	9.3	9.1	8.9	8.6	8.5	8.4	8.0	7.6	7.4	7.1	6.7	6.6
209.6	8.252										9.3	9.3	9.0	8.8	8.6	8.4	8.3	7.9	7.7	7.5	7.4	7.0	6.7
215.9	8.500										9.3	9.3	9.0	8.8	8.6	8.4	8.3	7.9	7.7	7.5	7.4	7.0	6.7
219.1	8.626											9.3	9.0	8.8	8.5	8.4	8.2	8.1	8.0	7.8	7.6	7.2	6.8
222.3	8.752											9.3	9.0	8.8	8.5	8.4	8.2	8.1	8.0	7.8	7.6	7.2	6.8
228.6	9.000											9.2	8.9	8.7	8.5	8.4	8.2	8.1	8.0	7.7	7.4	7.0	6.7